

The CVA-118 is a high-performance, compact 18-inch active subwoofer with 700 watts of efficient power output. The legendary Cerwin-Vega woofer design is reflected in this 18-inch woofer offering maximum bass performance with extreme power handling and exceptional low-frequency response. The CVA-118 features built-in amplification for an integrated, all-in-one solution with a powerful 1400 watts of peak power output. A unique and striking cast aluminum grille protects the woofer from, while doubling as a heat-sink to minimize power compression and optimizing driver performance. Housed in a compact hardwood enclosure design the size of a standard 15-inch subwoofer footprint, the CVA-118 is highly portable and durable with the option of a durable Coolex® polyurethane paint or high-grade black carpet finish. Along with XLR and 1/4" TRS connectors, the CVA-118 has Master/Slave output connectors that allow for multiple CVA subwoofers to be daisy-chained together using a single signal. This compact active sub also features a 35 mm pole-mount socket to accommodate a satellite speaker for full range performance.



The Details

Specifications

Feature	Advantage	Benefit
Legendary Cerwin-Vega Bass Performance	best-in-class, top-grade system design	quality low frequency and full body bass response
Custom 18-inch Cerwin-Vega Woofer	highly qualified, customized woofer design	extreme power handling and exceptional cone excursion
Built-in System Amplification	amplifier designed to optimize 18-inch woofer performance	truly portable and flexible all-in-one system
Master/ Slave Output	allows for daisy-chaining multiple subs	reduces cable connections, and system expansion
Cast Aluminum Grille	durable grille design that protects the woofer and acts as a heat sink	reduces power compression so you can play louder and longer
Hardwood Enclosure with Paint or Carpet Finish	rugged enclosure construction material with optional finish	reliable cabinet that will last through harsh conditions
Top-mount 35 mm Pole Socket	accommodates a satellite speaker for full range performance	allows for flexible full range system configurations

Power:	continuous 700 watts peak 1400 watts
Frequency Response:	41 Hz - 135 Hz (±3 dB)
Frequency Range:	38 Hz - 135 Hz (-10 dB)
Max SPL:	131 dB
Crossover:	LPF 65 Hz - 130 Hz HPF 35 Hz
Connectors:	inputs XLR/F Balanced (x2) 1/4" TRS (x2) outputs XLR/M (x2) XLR/M Slave
Controls:	HPF 65 Hz, 85 Hz, 130 Hz variable LPF 65 Hz, 130 Hz polarity 0 - 180 degrees
Driver:	model, SW18C, size 18"
Voice Coil:	3"
Enclosure / Finish	Hardwood Coolex® Paint or Black Carpet
Dimensions:	25.0" x 21.0" x 23.5" 635 mm x 533 mm x 597 mm
Weight:	subwoofer 115 lb (52.2 kg) shipping 121 lb (54.8 kg)